

Technical information on PrintGuardPlus

Sheet material

I. Installing PrintGuardPlus

Make sure that the cylinder's surface is free of grease, because grease impairs adhesion.

II. Care and maintenance of PrintGuardPlus

PrintGuardPlus is a durable anti-marking sheet with a permanent cross-linked silicone coating. It usually lasts 6 to 12 months, depending on use and care. To lengthen its life, we recommend removing any ink build-up immediately. Do not allow the ink to dry, because dry ink is hard to remove, and scrubbing can damage the surface of PrintGuardPlus.

Use a mild detergent (such as All) and thin it 50% with water. Use a lint-free polishing cloth or preferably a sponge. Then clean the surface with the moist cloth or sponge, applying light, uniform pressure.

Never use a screwdriver, knife or any sharp or abrasive tool on the PrintGuardPlus surface. Avoid continuous excessive scrubbing on one spot, because this will destroy the PrintGuardPlus glass bead structure. Gentle, consistent pressure does not distort the sheet.

Another special note on cleaning your PrintGuardPlus:

Due to the sheet's special coating, ink can remain in the gaps of the glass bead structure. This causes the orange surface of PrintGuardPlus to darken with time. This darkening in no way impairs your sheet's anti-marking properties!

That is how to clean your PrintGuardPlus very quickly and easily. It is also the way to maintain the sheets' ink-repellent silicone layer.

III. Safety precautions

When installing the sheet manually or with tools, please make sure that the machine is in the "Off/Stop" position before approaching its rotating parts.

If you have technical questions, please contact:

CITO-SYSTEM GmbH

0911 95885-0