




CITO FAST Rubber

Efficient ejection profile – for uniform, excellent quality

- Especially developed for cutting dies both for diemakers and converters of solid and corrugated board
- Constant ejection force even at **full machine speeds** and **high runs**
- **UV and ageing-resistant** material
- Available as **self-adhesive EasyFix version** for exact positioning and residue-free removal of the ejection material
- Certified as **safe for the production of folding boxes for food packaging**






The efficient rubber profile stands out due to its constant and excellent quality, for up to 2 million impressions or more and full machine speed. In addition, CITO FAST Rubber is ideal for use with corrugated board to crush fluting at the edge of the tuck-in flaps. The material is UV and ageing-resistant.

By conforming to EU Regulation No. 1935/2004 for food contact materials, Articles 3 and 17, CITO FAST Rubber is safe for the production of folding cartons for food packaging.

The self-adhesive EasyFix version allows you to precisely position the ejection material on your cutting die, as well as residue-free removal of the rubbering. The surface of your cutting die remains undamaged. Use of activator sprays and super glues is avoided; this means improved safety in your company.

Technical data



	CITO FAST Rubber
Hardness – Shore A	70 (±5)
Service life	≥ 2 m
Decompression*	0.20 sec
Operating speed	≤ 5 Hz
UV stability	100 %

* complete discharge after 30 % compression in seconds

Description	Colour	Dimensions (L × W × H)	Order no.	EasyFix Order no.
Strips (unit = 100 strips), 70 Shore A				
CITO FAST Rubber	WHITE	700 × 3.0 × 7.3 mm	BPB00231	
CITO FAST Rubber	WHITE	700 × 5.0 × 7.3 mm	BPB00205	BPB01205
CITO FAST Rubber	WHITE	700 × 5.0 × 9.5 mm	BPB00229	BPB01229
CITO FAST Rubber	WHITE	700 × 8.0 × 7.3 mm	BPB00212	BPB01212
CITO FAST Rubber	WHITE	700 × 8.5 × 9.5 mm	BPB00228	BPB01228



Further information
on CITO FAST Rubber:
www.cito.de/fast-rubber