

Technical Data Sheet

CITO D/12 EasyFix



Use

Intended use

Profiles for optimum conversion of multi-flute corrugated board for use on perforation lines and cutting/creasing combinations on the cutting die in packaging production.

Profiles in this product range are self-adhesive profiles with CITO EasyFix adhesive technology and can be quickly and precisely applied to cutting dies.

CITO EasyFix technology prevents the position from shifting during the diecutting process and securely withstands the stresses during the diecutting process.

Products with CITO EasyFix can be removed from most wooden surfaces without leaving any residue.

Product features



- Colour-coded heights
- CITO EasyFix technology
- With Fingerlift
- ISEGA certified
- Certified as safe for the manufacture of folding cartons for food
- Compliant with Regulation (EC) No. 1935/2004 for food contact materials, Articles 3 and 17

Delivered form

Strips

Composition/Material

TPE, adhesive tape with protective paper

Hazardous substance

No

RoHS compliant

Yes

REACH compliant

Yes

SVHC

The product contains bumetrizole (CAS No. 3896-11-5) in a concentration greater than 0.1 % by weight. When used as intended, there is no danger to humans or the environment.

SCIP No: dcede560-26ba-441a-aed0-0f750b9f431a

Typical properties

Solid, dry

Recommended storage/duration

3 years after the date of production if stored correctly.

Temperature: 15–25 °C; Humidity: 50–70 %

Waste code

20 03 01 – mixed municipal waste

Give preference to recycling over disposal.

Customs tariff number

39169050

Country of origin

European Union



Technisches Datenblatt

CITO D/12 EasyFix

Anwendung

Bestimmungsgemäße Verwendung

Profile zur optimalen Verarbeitung von mehrwelliger Wellpappe für den Einsatz an Perforationslinien und Schneid-Rill-Kombinationen auf der Stanzform in der Verpackungsherstellung.

Profile dieser Produktreihe sind selbstklebende Profile mit CITO EasyFix-Klebertechnologie und können schnell und präzise auf Stanzformen aufgeklebt werden.

Die CITO EasyFix-Technologie verhindert ein Verschwimmen der Position im Stanzprozess und hält den Belastungen während des Stanzprozesses sicher stand.

Produkte mit CITO EasyFix lassen sich von den meisten Holzoberflächen rückstandsfrei entfernen.

Produktmerkmale



- Farbcodierte Höhen
- CITO EasyFix-Technologie
- Mit Fingerlift
- ISEGA-zertifiziert
- Zertifiziert als unbedenklich für die Herstellung von Faltschachteln für Lebensmittel
- Konform mit Verordnung (EG) Nr. 1935/2004 für Lebensmittelkontaktmaterialien Artikel 3 und 17

Lieferform

Streifen

Zusammensetzung/Material

TPE, Klebeband mit Schutzpapier

Gefahrstoff

Nein

RoHS-konform

Ja

REACH-konform

Ja

SVHC

Das Produkt enthält Bumetrizol (CAS-Nr. 3896-11-5) mit mehr als 0,1 % Gewichtsanteil. Bei bestimmungsgemäßer Verwendung besteht keine Gefahr für Mensch und Umwelt.

SCIP-Nr: dcede560-26ba-441a-aed0-0f750b9f431a

Typische Eigenschaften

Fest, trocken

Empfohlene Lagerung/Dauer

3 Jahre nach dem Produktionszeitpunkt bei fachgerechter Lagerung.
Temperatur: 15–25 °C; Luftfeuchtigkeit: 50–70 %

Abfallschlüssel

20 03 01 – gemischte Siedlungsabfälle
Die Wiederverwertung (Recycling) ist der Entsorgung vorzuziehen.

Zolltarifnummer

39169050

Ursprungsland

Europäische Union